

## DISPLAY UNITS REFRIGERATED



### FEATURES

- Temperature range +2°C to +8°C at ambient temperature of 32°C
- Unit provided with 2 adjustable shelves
- Illuminated shelf and base for perfect product presentation
- Digital display and temperature control for high accuracy
- Automatic defrost
- Low noise
- Double glazed heated glass windows to prevent condensation
- Grade 304 Stainless Steel interior
- Castor wheels make the unit easy to move
- Double glazed glass windows to prevent condensation

### SPECIFICATIONS - DFC0900

CAPACITY:	225Lt
SHELVES:	3
POWER:	0.580kW
VOLTAGE:	230V - 50Hz
DIMENSIONS:	900 x 730 x 1200mm
WEIGHT:	220kg



### SPECIFICATIONS - DFC1200

CAPACITY:	310Lt
SHELVES:	3
POWER:	0.705kW
VOLTAGE:	230V - 50Hz
DIMENSIONS:	1200 x 730 x 1200mm
WEIGHT:	270kg



### SPECIFICATIONS - DFC1500

CAPACITY:	395Lt
SHELVES:	3
POWER:	0.855kW
VOLTAGE:	230V - 50Hz
DIMENSIONS:	1500 x 730 x 1200mm
WEIGHT:	330kg



### ORDER CODES:

- DFC0900 DISPLAY UNIT FRIDGE SALVADORE - F/STAND AZZURO - 900mm
- DFC1200 DISPLAY UNIT FRIDGE SALVADORE - F/STAND AZZURO - 1200mm
- DFC1500 DISPLAY UNIT FRIDGE SALVADORE - F/STAND AZZURO - 1500mm

